



CompostMat Forza

Tunnel Net Phase II & III

Technical data sheet

Product description

Type of product	Woven Fabric	Application	Indoor
Colour	Black/White	Polymer	PP and UHMWPE

Properties

Mechanical Properties	Standard	Performance	Tolerance
Tensile strength - Warp	Calculated strength	539 kN/m	-53,9 kN/m
Tensile strength - Weft	EN ISO 10319	80 kN/m	-8 kN/m
Air permeability	ISO 9237	828 l/(m ² *s)	-82,8 l/(m ² *s)
Elongation at break - Warp	EN ISO 10319	-	-
Elongation at break - Weft	EN ISO 10319	10 %	-2,3 %
Shrinkage	2h at 70°C	≤3 %	-

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	877 g/m ²	±43,85 g/m ²
Length		As required	-
Width		310-410 cm	±2 cm

The Quality Management System of IFG Cresco has been approved to the ISO 9001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.

IFG Cresco, a division of IFG Exelto N.V.

Weverslaan 15, 9160 Lokeren Belgium

T: +32 (0) 9 340 98 11 / F: +32 (0) 9 348 77 02

info@phormium.com / www.phormium.com