



Phormium
Growth driven. Future proof.

CompostMat

Tunnel Net Phase III

Technical data sheet

Product description

Type of product	Woven Fabric	Application	Indoor
Colour	Black	Polymer	100% Polypropylene

Properties

Mechanical Properties	Standard	Performance	Tolerance
Tensile strength - Warp	#N/A	320 kN/m	-32 kN/m
Tensile strength - Weft	EN ISO 10319	80 kN/m	-8 kN/m
Air permeability	ISO 9237	817 l/(m ² *s)	-81,7 l/(m ² *s)
Elongation at break - Warp	EN ISO 10319	30 %	-6,9 %
Elongation at break - Weft	EN ISO 10319	10 %	-2,3 %
Shrinkage	2h at 70°C	≤3 %	-

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	800 g/m ²	±40 g/m ²
Length		As required	-
Width		310-410 cm	±2 cm

The Quality Management System of IFG Cresco has been approved to the ISO 9001 / ISO 14001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.



BQA_QMS019_C_2017734



BQA_EMS_C_2020734



019 - QMS



019 - EMS

IFG Cresco, a division of IFG Exelto N.V.

Weverslaan 15, 9160 Lokeren, Belgium

T: +32 (0) 9 340 98 11 / F: +32 (0) 9 348 77 02

info@phormium.com / www.phormium.com