

# PhormiCool 137

Ground Cover

## Technical data sheet

### Product description

<b>Type of product</b>	Woven Fabric	<b>Application</b>	Outdoor
<b>Colour</b>	Grey w/ lines every 25 cm	<b>Polymer</b>	100% Polypropylene

### Properties

Mechanical Properties	Standard	Performance	Tolerance
Tensile strength - Warp	EN ISO 10319	27 kN/m	-2,7 kN/m
Tensile strength - Weft	EN ISO 10319	24 kN/m	-2,4 kN/m
Elongation at break - Warp	EN ISO 10319	25 %	±2,5 %
Elongation at break - Weft	EN ISO 10319	20 %	±2 %
Water permeability	EN ISO 11058	5 l/m <sup>2</sup> *s	-1,5 l/m <sup>2</sup> *s
Shrinkage	2h at 70°C	1 %	-

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	130 g/m <sup>2</sup>	±13 g/m <sup>2</sup>
Length		As required	-
Width		335-415-525 cm	±2 cm

Durability	Standard	Performance	Tolerance
UV Stabilization	Phormium test method	500 kLy	

### Warranty

#N/A

The Quality Management System of IFG Cresco has been approved to the ISO 9001 / ISO 14001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.



**IFG Cresco, a division of IFG Exelto N.V.**

Weverslaan 15, 9160 Lokeren, Belgium

T: +32 (0) 9 340 98 11 / F: +32 (0) 9 348 77 02

info@phormium.com / www.phormium.com