

PhormiSol 100 R

Ground Cover

Technical data sheet

Product description

Type of product	Woven Fabric	Application	Indoor
Colour	Black w/orange squares (25 cm)	Polymer	100% Polypropylene

Properties

Mechanical Properties	Standard	Performance	Tolerance
Tensile strength - Warp	EN ISO 10319	17 kN/m	-1,7 kN/m
Tensile strength - Weft	EN ISO 10319	11 kN/m	-1,1 kN/m
Elongation at break - Warp	EN ISO 10319	19 %	±1,9 %
Elongation at break - Weft	EN ISO 10319	11 %	±1,1 %
Water permeability	EN ISO 11058	15 l/m ² *s	-4,5 l/m ² *s
Shrinkage	2h at 70°C	1 %	-

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	100 g/m ²	±10 g/m ²
Length		As required	-
Width		105-131-167-207-262-335-415-525 cm	±2 cm

Durability	Standard	Performance	Tolerance
UV Stabilization	(Indoor use)	500 kLy	

Warranty

Five (5) years, see Phormiums limited warranty for all terms, conditions, and exclusions in writing.

The Quality Management System of IFG Cresco has been approved to the ISO 9001 / ISO 14001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.



IFG Cresco, a division of IFG Exelto N.V.

Weverslaan 15, 9160 Lokeren, Belgium

T: +32 (0) 9 340 98 11 / F: +32 (0) 9 348 77 02

info@phormium.com / www.phormium.com