

PhormiTex Lumina 60 O

Open sun shading screen

Technical data sheet

Product description

| | | | |
|------------------------|--------------|--------------------|--------------|
| Type of product | Woven Fabric | Application | Indoor |
| Colour | White | Material | PES/Modacryl |

Properties

| Physical Properties | Standard | Performance | Tolerance |
|---------------------|-------------|----------------------------|-----------------------|
| Weight | EN ISO 9864 | 77 g/m ² | ±7,7 g/m ² |
| Length | | As required | - |
| Roll Width | | 325-430-480-525 cm | ±2 cm |
| | | 127,9-167,3-187,0-206,7 in | ±0,8 in |

| Mechanical Properties | Standard | Performance |
|---------------------------|----------------------|-------------|
| Energy saving | Phormium test method | 25 % |
| Direct Light transmission | Phormium test method | 40 % |
| Shading | Phormium test method | 60 % |
| Shrinkage | 2h at 70°C | ≤1 % |

| Durability | Standard | Performance |
|------------------|-------------------------------|-------------|
| UV Stabilization | Phormium test method | 600 kLy |
| Flame retardant | DIN 4102 | |
| | NTA 8825 | Class 1 |
| | ASTM E 84 | |
| | NFPA 701 - 2015 Test Method 2 | |

Warranty

Under all types of greenhouse covering 6 years, see Phormiums limited warranty for all terms, conditions, and exclusions in writing.

Remarks

The Quality Management System of IFG Cresco has been approved to the ISO 9001 / ISO 14001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.



BQA_QMS019_C_2017734



BQA_EMS_C_2020734



019 - QMS



019 - EMS

IFG Cresco, a division of IFG Exelto N.V.

Weverslaan 15, 9160 Lokeren, Belgium

info@phormium.com / www.phormium.com