

# PHL Wit

## Darkening gable screen

### Technical data sheet

#### Product description

<b>Type of product</b>	Laminated woven fabric	<b>Application</b>	Indoor
<b>Colour</b>	White	<b>Material</b>	100% Polyethylene

#### Properties

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	209 g/m <sup>2</sup>	±20,9 g/m <sup>2</sup>
Length		As required	-
Roll Width		190-210-230-250-270 cm	±2 cm
		74,8-82,7-90,5-98,4-106,3 in	±0,8 in

Mechanical Properties	Standard	Performance
Energy saving	Phormium test method	60 %
Direct Light transmission	Phormium test method	0 %
Shading	Phormium test method	100 %
Shrinkage	2h at 70°C	≤1 %

Durability	Standard	Performance
UV Stabilization	Phormium test method	600 kLy
Flame retardant	DIN 4102	-
	NTA 8825	-
	ASTM E 84	-
	NFPA 701 - 2015 Test Method 2	-

#### Remarks

-
---

The Quality Management System of IFG Cresco has been approved to the ISO 9001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.

#### IFG Cresco N.V.

Weverslaan 15, 9160 Lokeren, Belgium

info@phormium.com / www.phormium.com