

PhormiTex Noctis

Assimilation screen

Technical data sheet

Product description

Type of product	Woven Fabric	Application	Indoor
Colour	White	Material	PE/Acryl

Properties

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	128 g/m ²	±12,8 g/m ²
Length		As required	-
Roll Width		400-430-480-530 cm	±2 cm
		157,5-169,3-189,0-208,7 in	±0,8 in

Mechanical Properties	Standard	Performance
Energy saving	Phormium test method	42 %
Direct Light transmission	Phormium test method	1,7 %
Shading	Phormium test method	98,3 %
Shrinkage	2h at 70°C	≤1 %

Durability	Standard	Performance
UV Stabilization	Phormium test method	600 kLy
Flame retardant	DIN 4102	
	NTA 8825	-
	ASTM E 84	
	NFPA 701 - 2015 Test Method 2	

Warranty

Under all types of greenhouse covering 6 years, see Phormiums limited warranty for all terms, conditions, and exclusions in writing.

Remarks

The Quality Management System of IFG Cresco has been approved to the ISO 9001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.

IFG Cresco, a division of IFG Exelto N.V.

Weverslaan 15, 9160 Lokeren Belgium
info@phormium.com / www.phormium.com