

PhormiTex Super

Energy saving screen

Technical data sheet

Product description

Type of product	Woven Fabric	Application	Indoor
Colour	Diffuse	Material	HDPE/Modacryl

Properties

Physical Properties	Standard	Performance	Tolerance
Weight	EN ISO 9864	73 g/m ²	±7,3 g/m ²
Length		As required	-
Roll Width		325-430-480-530 cm	±2 cm
		127,9-167,3-187,0-208,7 in	±0,8 in

Mechanical Properties	Standard	Performance
Energy saving	Phormium test method	47 %
Direct Light transmission	Phormium test method	85 %
Shading	Phormium test method	15 %
Shrinkage	2h at 70°C	≤1 %

Durability	Standard	Performance
UV Stabilization	Phormium test method	600 kLy
Flame retardant	DIN 4102	B1
	NTA 8825	Class 1
	ASTM E 84	
	NFPA 701 - 2015 Test Method 2	

Remarks

-

The Quality Management System of IFG Cresco has been approved to the ISO 9001 Quality Management System Standard. Certificates are available on request.

The information set forth in this data sheet reflects the best knowledge at the time of publication. The document is subject to change pursuant to new developments and findings. The same reservation applies to the properties of the products described. No liability is undertaken for results obtained by usage of the products and information.

IFG Cresco N.V.

Weverslaan 15, 9160 Lokeren, Belgium

info@phormium.com / www.phormium.com